

94CD/USB 8 Digit DigiBus Desktop Switchboard Station



The Elvox® 945CD/USB is a software based switchboard master for the DigiBus System. The 945CD/USB used in conjunction with model 6201 handset, computer and touch screen provides conversation with apartment stations and door entry panels. A Windows based interface annunciates calls, F1-F8 emergency/alarm signals by apartment code and tenant name. Activity log stores all system activity with a time/date stamp for future reference. Call signaling is user definable using .wav files. Easy call and answering procedures provide error free communication system.

General Information		Specifications	
-Touch Screen Operation	Configuration:	1 –4 switchboards per system	
-Alpha-numeric Directory	Controls:	Door Release/Relay Activation Call transfer/conference Diagnostics Print Configuration	
-Remote Relay Activation	Handset:	6201 Handset Required (ordered separately)	
-Call Transfer/Conference Operation	Interface	Touch screen Recommended (not included in 94CD/USB)	
-Call/Event Logging	Computer Requirements	Pentium with available serial port Windows XP home or Professional (Not included in 94CD/USB)	
-Customizable Tones	Power Supply:	6941/C17-6948/C17 (depending on system configuration)	
-Apartment Station Diagnostics			
-For use with all DigiBus Components			
-Remote Access			
-Door Alarm/Event monitoring			

94CD/USB
 Software Based DigiBus Switchboard

Architects and Engineers Specification

The Switchboard master shall be Elvox® 94CD/USB. The switchboard shall be a software based master utilizing a Windows PC and Touch screen. The Switchboard shall provide conversation with apartment stations and door entry panels. The Touch Screen display shall annunciate both incoming and outgoing calls and alarms in a simple English language format. Unanswered call shall be queued. Signaling shall be customizable utilizing >wav files. Switchboard shall provide simple call and answering procedures and integral alphanumeric directory with building management functions. Call transfer, call conference and interphone diagnostics shall shall be easily accomplished from the main display. Remote lock and relay control shall be provided with single touch option,

94CD/USB